



EUROCONTROL

Conta banconote con funzioni di rilevamento falsi e filo metallico. Ampio display retro illuminato con visualizzazione di 5 cifre risultati del conteggio delle banconote.

Alimentatore da 150 a 200 banconote o bollette con spessori da 0,06 a 0,15 mm. Capacità di conteggio fino a 1.000 unità al minuto.

Caratteristiche	Specifiche
<i>Sheets counting function and BATCH counting function .</i>	1) Ambient Temperature: 0°C- 40°C
1) ADD function	2) Ambient Humidity: 25% - 80%
2) Batch function	3) Feed System: Roller Friction System
3) Half note detection	4) Hopper Capacity: 150 old bills or 200 new bills
4) Chain note detection	5) Stacker Capacity: 150 old bills or 200 new bills
5) Double-note detection	6) Size of Countable Bills: 40mm X 110mm - 100mm X 175mm
6) Width detection function	7) Thickness of Countable Bills: 0.06mm - 0.15mm
7) UV counterfeit detection (option)	8) Large LCD display with blue background: Counting result display: 5 Digits; Batch preset number display: 3 Digits
8) MG counterfeit detection (option)	10) Remove Display: Three Digits LED.
9) Metal thread detection (option)	11) Power Source: Single Phase 110 V jÀ 10% RMS, 50 - 60 Hz; Also available in 220 V jÀ10% RMS, 50 - 60 Hz
10) Inferred character detection (option)	12) Power Consumption: < 55 W
	13) Counting Speed: 1,000 notes/min
	14) Certification: CE, ROHS approved